



QI-3024 ECO[®]

HIGH-TECH PERFORMMANCE

HIGH EFFICIENCY

3KW SOLAR INVERTER

DC INPUT 24V-100A

MAX SOLAR V 500VDC



BELONGS TO NATURE



Parameters

Model	QI-3024 ECO
AC Input voltage	220VAC (standard)
Input voltage range	90-280VAC±5V (Normal Model) 185-264VAC ±3V (UPS Model)
Input frequency	50/60Hz±5%
Out put power	6000VA 3000W
AC model output Voltage	220V±10%
Battery model output frequency	The output frequency under the mains is the same as the input frequency
Battery model output voltage	220VAC±3%
Battery model output frequency	50HZ or 60HZ±1%
Battery model output wave	Pure sine wave
Battery type	External lead-acid ,Gel, water or Lithium battery
Battery voltage	24VDC
Battery charging voltage	28.2VDC
Floating Charging Voltage	27VDC
Max pv input voltage	500VDC
Mppt tracking range	30-500VDC
Maximum solar charging current	100A
Maximum AC Charge Current	60A
Battery charging voltage range	24-28.2VDC
Transfer time	≤10ms(UPS Model)/ ≤20ms(INV Model)
load peak ratio	(MAX) 3:1
Protective function	Under the mains input overcurrent fuse Under inverter: overload protection, short circuit protection, low voltage protection,(with battery anti-reverse connection,board).
Status Display	You can view parameters such as AC voltage, AC frequency, PVvoltage, PV current, output voltage,output frequency, battery voltage, load current and other parameters by turning the page keys.
Voice prompt	<p>Low battery protection buzzer long beep Low battery buzzer beeps every second Machine fault buzzer beeps Overload buzzer beeps</p> <p>When the overload is less than 130%, the buzzer will sound every second,and the output will be turned off after 30S. When the overload is greater than 150%, the output willbe turned off after 300mS.</p>
Operating temperature	-10 ~ 50
Storage temperature	-15 ~ 45
Relative temperature	-10 ~ 90 no condensation
Noise	<50dB